



# CS-9018 Cutter/Stacker

Laser Printer Accessory



# CS-9018

**Fast. Reliable. Time-Saving Convenience.**

## Streamlined Features

- Self-contained, continuous form ticket handling
- Slit, cut & sequentially stack tickets at 235,000 per hour<sup>1</sup>
- Automatic top-of-form registration
- 2-line, 40-character LCD display
- Double-cut capability for clean-edge tickets
- Up to 59 feet per minute<sup>2</sup>
- Variable speed capability<sup>3</sup>
- Stores up to 99 ticket configurations
- Removable/interchangeable slitter assemblies
- Operator-friendly controls
- Quick & easy batch separation
- Increased productivity
- Automatic time-out circuit
- Cross cut knife and slitter assemblies easily replaced by user to maintain production

## Industry Applications

- Apparel Tags
- Price Labels
- Furniture Tags
- Routing Labels
- Mailing Labels
- Shelf Labels

<sup>1</sup> Requires optional slitter assembly

<sup>2</sup> Dependent on ticket length

<sup>3</sup> Model year 2020 and later up to 36% faster

# GENERAL SPECIFICATIONS / CS-9018

STOCK SPECIFICATIONS			
Media Size	Width	6-18 inches (152.4-457 mm) / Pin feed 0.5 inches (12.7 mm) per side	
	Thickness	Maximum 20 mil	
Ticket Size <sup>4</sup>	Length	2-4.5 inches (51 - 114.3 mm)	
	Width	1.25-3.5 inches (31.75 - 88.9 mm) <i>Special order minimum of 1.0" (25.4 mm)</i>	
Stacker Capacity	38 inches (965.2 mm) or approximately 3,500 tickets @ 11 mil		
THROUGHPUT (Variable - dependent on speed selection, ticket length and number across)			
Tickets Per Hour	5 Across	47,000 <sup>5</sup> tickets per hour @ 3 inches x 4.5 inches (76.2 mm x 114.3 mm)	59 ft/min
	11 Across	116,000 <sup>5</sup> tickets per hour @ 1.5 inches x 3.5 inches (38.1 mm x 88.9 mm)	51 ft/min
	13 Across	153,000 <sup>5</sup> tickets per hour @ 1.25 inches x 2.75 inches (31.75 mm x 69.9 mm)	44 ft/min
	17 Across	227,000 <sup>5</sup> tickets per hour @ 1 inch x 2 inches (25.4 mm x 50.8 mm)	36 ft/min
LCD DISPLAY			
Format	2 lines, 40 characters		
Content	Ticket count, speed and throughput		
Configurations	Up to 99 programmable ticket configurations		
Error Messages	Full array of error messages: JAMS, STACKER FULL, COVER OPEN, PAPER OUT		
Language Support	English, Spanish, Italian and German		
SAFETY FEATURES			
Auto System STOP	Activated if protective covers are not in place, paper out, stacker full or ticket jam		
Manual STOP Switch	Manual and Emergency STOP Switches		
ELECTRICAL/ENVIRONMENTAL/PHYSICAL			
Power Supply	220 VAC/60 Hz, single phase 20 AMP		
Acoustic	78 Dba		
Dimensions	78 inches (1981.2 mm) W x 31 inches (787.4 mm) D x 43 inches (1092.2 mm) H		
Weight	462 lbs (209.5 kg)		
OPTIONS			
Slitter	Interchangeable slitter modules, including special design for small width of 1-1.5 inches (25.4 - 38.1 mm)		
Control	Loop control for inline operation, feed with stop / start as input loop varies		
Waste Collection	Additional waste collection bins for quick swap		
Knives	Replacement and refurbished cross cut and slitter assemblies available for operator replacement		

<sup>4</sup> The recommended ticket size is a ratio where the length is greater than 1.3 times the width.

<sup>5</sup> Model year 2020 and later

## SATO AMERICA CORPORATE

10350-A Nations Ford Rd  
Charlotte, NC 28273

Phone: (704) 644-1650

sales-sallc@sato-global.com

## LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA  
CANADA CARIBBEAN

[www.satoamerica.com](http://www.satoamerica.com)